



EZ Clean Machine Mount JIT Resin Hopper

Seamless Switchovers, Minimize Potential Contamination

Introducing the ultimate solution for frequent material changes: our new EZ Clean Machine Mount JIT Resin Hopper. Designed for the ultimate ease and efficiency, it ensures a contamination-free environment during material changeovers, enabling thorough cleaning without the need to detach from the machine. Embrace the future of hassle-free material management!

› EZ Clean with Leak-Proof Teflon Seal

Our Discharge Access Opening sets a new standard for ease and cleanliness in material handling. Featuring a Teflon-on-Teflon sliding surface, when paired with VRX receivers or GSL/XSL loaders, material changeovers are as simple as flipping a switch & sliding the unit into the clean-out position.

› Slide & Lock Base

Ensures staff safety and operational precision.

› Maximized Capacity

Provides approximately 4 extra pounds of usable volume per size. 12, 16, & 20lb Configurations with Full Sight Glass Demand Adjustability



Plus

- › Borosilicate Glass View Chamber
- › Rigid Construction
- › 5-Year Manufacturer's Warranty



Sliding Base Receiver
In Operation Mode



Sliding Base Receiver
In Clean Out Mode

Optional:

- Optional photo-eyes or capacitance sensor for resin "volume fill" control.
- Standard with Non-Ferrous Contact Construction,
- Optional Stainless Steel Contact Available

Available:

- Currently Available for the VRX w/3DF & GSL/XSL Product Series
- Available in 12lb, 16lb, and 20lb JIT Sizes
- Available in 6" Flange w/2" Opening or 7" Flange w/3.5" Opening

EZ-Clean JIT Glass Machine Mount Hopper

Machine Mount Packages								
Part Number	Height		Capacity		Discharge Diameter		Shipping Weight	
	in	cm	lb	kg	in	cm	lb	kg
GMM-VRX-12-EZC	18.4	46.6	12.0	5.4	2.0	5.1	20.0	9.1
GMM-VRX-12-EZC-7F	17.1	43.5	12.0	5.4	3.5	8.9	21.0	9.5
GMM-VRX-16-EZC	22.4	56.8	16.0	7.3	2.0	5.1	22.0	10.0
GMM-VRX-16-EZC-7F	21.1	53.7	16.0	7.3	3.5	8.9	23.0	10.4
GMM-VRX-20-EZC	25.4	64.4	20.0	9.1	2.0	5.1	23.0	10.4
GMM-VRX-20-EZC-7F	24.1	61.3	20.0	9.1	3.5	8.9	24.0	10.9

-Stainless Steel Contact (-SS) configurations available, add ~10-12lbs to shipping weight.

-For use with any Novatec product with 3" low-profile discharge (VRX-12/19/30, VRX-38 w/discharge swap, GSL/XSL)

-Photo-eyes sold separately as optional demand volume adjustment.

-All units come with blank Mounting flange. Bolt-pattern to be specified by customer or added in the field.

GMM-VRX-XX-EZC(-SS) & GMM-VRX-XX-EZC-7F(-SS)

